

CONSTRUCTION

Hull, deck and ancillary mouldings are constructed in heavy duty hand lay-up GRP. Isopthalic resin is used in the hull which is stiffened below the waterline by bonded-in bulkheads and longitudinal stringers. The main underfloor areas are foamed and the cockpit is self-draining. Above the waterline the hull is stiffened by ribs in the cockpit area and by a GRP module in the cabin. The one piece deck moulding is fixed to the hull with marine grade fastenings.

HULL AND DECK FITTINGS

Stainless steel winch eye, galvanised keel and bilge keel bands. Anodised alloy bow roller, mooring cleat and stern cleats. Stainless steel handrails from wheelhouse to foredeck. Toughened glass windows to front and side of wheelhouse with single perspex window in bulkhead aft of steering position. Fitted bilge pump, Push/pull steering to suit through pivot steering outboards (Note: Standard steering cable suits single outboard installation for twin engines consult your dealer).

ACCOMMODATION

Enclosed cuddy/cabin with 2 berths/bench seats and stowage lockers under. Wheel steering to starboard. Helmsman and co pilot's seats with cushions. Lockable cabin door.

PART BUILT BOATS

We have always offered our fishing boats as mouldings to professional and amateur boat builders for completion to their own specifications. These mouldings can be supplied at any stage from bare hull shells upwards. We are pleased to quote for the supply of additional items from our range of components and fittings.

COLOURS


Hull: Dark blue Deck: Off white Special colours available at extra cost.

DELIVERY CHARGES

Prices quoted for standard and part built boats and mouldings include the cost of delivery from our works to our approved point of sale dealers on the UK Mainland only. Delivery may be charged for urgent orders or for accessories and trailers ordered and/or delivered separately, and for boats delivered outside the UK Mainland.



TT BOAT DESIGNS The all new Day Angler 19+ is the result of DAY ANGLER 19+ design collaboration between Orkney and 19'6" 5.95 m TI Boat Designs: TI are best known for LOA 7'6" 2.29 m Beam their Nelson launches and Pilot boats. 1650 lbs 750 kg Weight Nelsons are used by many of the world's Single or Twin Outboard Engine options harbour and port authorities for year Max power 65 HP round operation in all conditions: 23 knots Max speed Inevitably the new 19 displays excellent 15 knots Optimum speed sea keeping ability which together with Performance indicator 30 HP 12 knots the big working cockpit and sheltered 17 knots 50 HP (Estimated) helm position make it ideal for both the 65 HP 23 knots sea angler and commercial user. Average cockpit 6'10" x 6'2" = 42 sq ft dimensions 2.09m x 1.88 m = 3.82 sg m General Arrangement showing optional pulpit, mast navigation lights and windows in aft bulkhead.





Orkney Boats Ltd, Ford Lane Industrial Estate, Yapton, Arundel, Sussex BN18 ODF Telephone: 01243 551456 Fax: 01243 551914

Please note that performance indicators are approximate, dependent on poylood and not guaranteed. Lengths quoted are hull lengths only and other data is for general guidance. All weights and measurements are approximate. Drawings may show boats fitted with optional equipment. If your application is unusual or particularly arduous please consult us or your dealer to ensure that you get the right boat for the job.